



DELO[®] TORQFORCE SYN

(Formerly: Chevron Arctic Drive Train Fluid)

SAE 5W-20

PRODUCT DESCRIPTION

Delo[®] TorqForce Syn SAE 5W-20 is a high performance fully synthetic lubricant designed for use in transmissions and hydraulic systems.

CUSTOMER BENEFITS

Delo TorqForce Syn SAE 5W-20 delivers value through:

- **Long equipment life** — Special additives protect metal surfaces against scuffing and wear even under operating conditions of high temperature and high load.
- **Smooth operation** — Excellent frictional control helps prevent clutch slippage and assures quiet and efficient action of transmission and brakes while minimizing wear.
- **Extreme temperature performance** — Excellent cold weather pumpability in sub-zero/ arctic operating conditions. Very good high operating temperature performance for severe service applications.
- **Improved filterability** — Delo TorqForce Syn is formulated with special additive chemistry that allows for ultra-fine filtration which provides exceptional fluid cleanliness and equipment reliability performance. Delo TorqForce Syn can achieve cleanliness levels down to 18/16/13 and potentially cleaner with appropriate Chevron approved ISOCLEAN[®] Programs.
- **Minimal downtime** — Good compatibility with seals, O-rings, and packing materials maintains their good condition and keeps leakage at a minimum.
- **Long oil life** — Outstanding ability of the synthetic base stock to withstand oxidation at high operating temperatures resulting in long service life for the oil.

- **Reliable operation** — Formulation helps keep metal parts clean and free of varnish and sludge deposits that could result in premature breakdown.
- **Minimizing weather and storage concerns** — Protects against rust and corrosion of highly finished precision parts when operating in humid conditions and during seasonal shutdown periods.
- **Warranty Plus protection** — Bumper-to-bumper warranty protection from the engine to the drive train. Payment for Chevron lubricant-related damage to your equipment, including parts and labor.¹ Problem resolution and technical advice from Chevron's lubrication experts.

FEATURES

Delo TorqForce Syn SAE 5W-20 is a high performance lubricant designed for use in transmissions and hydraulic systems operating in arctic conditions and requiring a fluid meeting Caterpillar TO-4 or Allison C-4 requirements. It is also recommended for transmission and hydraulic systems manufactured by Dana Powershift, Komatsu, Komatsu Dresser, Tremec/ TTC, Vickers and ZF.



Delo TorqForce Syn SAE 5W-20 is manufactured using fully synthetic base oils, detergents, dispersants, oxidation and corrosion inhibitors, anti-wear and extreme pressure agents, and a foam suppressant.

Delo TorqForce Syn SAE 5W-20 offers excellent friction retention, wear control, seal compatibility, oxidation stability, and viscosity stability. The frictional characteristics of the fluid are retained over the life of the lubricant.

¹ See Warranty Plus for details and restrictions.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

20 May 2015
TTF-33

© 2015 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark, Delo, ISOCLEAN, ISOSYN and the ISOSYN logo are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

Components are protected from wear, even under high load conditions by controlling the formation of corrosion, varnish, and sludge.

Delo® TorqForce Syn SAE 5W-20 is designed for both newly developed and older model drive train components. Delo TorqForce Syn SAE 5W-20 provides high performance throughout the seasons, maintaining optimal stability in a wide range of ambient temperatures.

APPLICATIONS

Delo TorqForce Syn SAE 5W-20 is recommended for use in **Allison, Caterpillar, Dana Powershift, Komatsu, Tremec/TTC, Vickers** and **ZF** transmissions, wet brakes, and hydraulic systems operating in arctic conditions.

Delo TorqForce Syn SAE 5W-20 is not recommended for use in combined farm tractor hydraulic and transmission systems where low brake chatter is a requirement.

Delo TorqForce Syn SAE 5W-20 meets:

- service requirements of **Caterpillar** TO-4

Delo TorqForce Syn SAE 5W-20 is recommended for:

- **Dana Powershift**
- **Komatsu** KES 07.868.1
- **Komatsu Dresser**
- **Tremec/TTC**
- **Vickers** 35VQ25
- **ZF** TE-ML-03C

Do not use in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

TYPICAL TEST DATA

SAE Grade	5W-20
<i>Product Number</i>	293109
<i>SDS Number</i>	38363
API Gravity	35.2
Viscosity, Kinematic cSt at 40°C cSt at 100°C	39 7.5
Viscosity, Cold Crank, °C/Poise	-30/39
Viscosity Index	163
Flash Point, °C(°F)	244(471)
Pour Point, °C(°F)	-51(-60)

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.