



DELO[®] 400 ZFA

SAE 10W-30 (Synblend)



PRODUCT DESCRIPTION

“Delo. Let’s go further.[®]”

Delo[®] 400 ZFA SAE 10W-30 with ISOSYN[®] Advanced Technology is a premium synthetic blend fuel economy and mixed fleet engine oil recommended for naturally aspirated and turbocharged four-stroke diesel engines and four-stroke gasoline engines in which the API FA-4 or SN service category and SAE 10W-30 viscosity grade are recommended.

CUSTOMER BENEFITS

Delo 400 ZFA SAE 10W-30 (Synblend) with ISOSYN Advanced Technology is an API FA-4 heavy duty engine oil specifically formulated for on highway applications, including 2017 greenhouse gas (GHG 17) compliant diesel engines with lower CO₂ emissions and improved fuel economy, in addition to EPA 2010 compliant low emission diesel engines with Selective Catalytic Reduction (SCR), Diesel Particulate Filter (DPF) and Exhaust Gas Recirculation (EGR) systems calling for SAE 10W-30 heavy duty motor oil.

Delo 400 ZFA SAE 10W-30 with ISOSYN Advanced Technology is formulated to protect new generation GHG’17 model diesel engines.

Delo 400 ZFA SAE 10W-30 delivers value through:

- **Improved Fuel Economy** — Up to 1.3% improvement vs. SAE 15W-40 oils in Class 8 vehicle diesel engine bench testing programs.
- **Better Low Temperature Pumpability** — Excellent cold flow properties help with rapid oil circulation to minimize wear during cold temperature starting.

- **Exceptional Deposit Control** — Superb oxidation resistance, thermal stability and detergency minimize piston and turbocharger deposits.
- **Minimized Operating Costs** — Exceptional anti-wear, deposit and soot control. Cylinders, pistons, rings and valve train components are well protected against wear and corrosion, providing optimum service life and minimal maintenance. Contributes to maximum vehicle utilization and minimal downtime.
- **Excellent Emission Control System Life** — Provides optimum Diesel Particulate Filter (DPF) life for minimal downtime and cleaning, thus managing maintenance costs.
- **Managed Inventory Costs** — Suitable for use in four-stroke gasoline and naturally aspirated turbocharged and modern electronically controlled/low emission diesel engines where API FA-4 or SN performance oils are required. Allows users with a wide mix of engine brands to enjoy simplified inventory and dispensing systems that may contribute to saving money, space and handling time.
- **Warranty Plus Protection** — Bumper-to-bumper warranty protection from the engine to the drive train. Payment for Chevron lubricant-related damage to your equipment, including parts and labor.¹ Problem resolution and technical advice from Chevron’s lubrication experts.
- **Access to Chevron’s Lubrication and Industry Knowledge** — Helps maximize your bottom line business results.

¹ See Warranty Plus for details and restrictions.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

1 December 2016
HDMO-75

© 2013-2016 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark, Delo, Delo. Let’s go further., ISOSYN and the ISOSYN logo are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

FEATURES

Delo® 400 ZFA SAE 10W-30 with ISOSYN® Advanced Technology is formulated using advanced additive technology to provide outstanding protection and improved fuel economy for on-highway diesel engine applications that allow the use of an API FA-4 SAE 10W-30.

Delo 400 ZFA SAE 10W-30 is formulated with ISOSYN Advanced Technology, which is the combination of Chevron's industry-leading formulating expertise with unique, high performance additive chemistry to help extend the durability of critical engine parts.

ISOSYN ADVANCED TECHNOLOGY

ISOSYN Advanced Technology is the combination of Chevron's outstanding formulating expertise, unique high performance additive chemistry and premium base oils that helps extend the durability of critical diesel engine parts.

Delo 400 products formulated with ISOSYN Advanced Technology can provide improved engine longevity, extended oil drain performance, and excellent diesel component parts protection, helping to extend vehicle life and minimize total cost of ownership when compared with previous generation Chevron HDMO formulations.

ISOSYN Advanced Technology benefits customers by helping to provide:

- Up to 35% improved oil oxidation control*
- Up to 68% improved wear protection*
- Up to 46% improved piston deposit control*

*Results will vary based on the Delo 400 product, operating conditions, and engine types. Always follow OEM recommendations and utilize used oil analysis testing when extending oil drain intervals.

FUNCTIONS

Delo 400 ZFA SAE 10W-30 with ISOSYN Advanced Technology helps to keep rings clean and free for maximum combustion pressure and minimal wear. It minimizes valve and piston crown land deposits, thus managing oil consumption. Its high level of ashless dispersants keeps fuel soot in suspension and thus helps to avoid filter plugging, heavy cylinder head

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.



sludge, abrasive polishing wear, high viscosity increase, and oil gelling. These problems can result in excessive engine wear and bearing failure on startup, without prior indication to the operator.

Specially selected oxidation inhibitors control oxidation, sludge, and undue thickening. Its unique blend of extreme pressure anti-wear additives protect against valve train wear and scuffing of highly loaded parts operating under boundary lubrication. A specially selected viscosity index improver ensures easy flow at low temperatures and excellent film protection in hot engine areas. A defoaming additive protects against air entrainment.

The combination of premium dispersant additives and ISOSYN Advanced Technology allows Delo 400 ZFA SAE 10W-30 to effectively disperse soot and keep it in suspension. This minimizes the risk of valve train wear and filter plugging.

Applications

Delo 400 ZFA SAE 10W-30 with ISOSYN Advanced Technology is a fuel economy and mixed fleet engine oil recommended for naturally aspirated and turbocharged four-stroke diesel engines and four-stroke gasoline engines in which the API FA-4 or SN service categories and SAE 10W-30 viscosity grade are recommended. It is formulated for engines operating under severe service and in a wide range of climatic conditions.

Delo 400 ZFA SAE 10W-30 with ISOSYN Advanced Technology is formulated for exceptional performance with ultra low sulfur diesel (ULSD) and other low sulfur diesel fuels.

This product is recommended for use in:

- Today's most modern on-highway low emission designs, as well as some previous generation model diesel engines (Detroit Diesel DD15/DD13 EPA 13 and EPA 10 model diesel engines) that are authorized to use API FA-4 SAE 10W-30 engine oils.

Delo® 400 ZFA SAE 10W-30 is recommended for:

- **API Service Categories** FA-4, SN
- **Cummins** CES 20087
- **MB** 228.61
- **Detroit Fluids Specification (DFS)** 93K223

TYPICAL TEST DATA

SAE Grade	10W-30
<i>Product Number</i>	257003
<i>SDS Number</i>	42683
Density at 15°C, kg/L	0.867
Viscosity, Kinematic mm ² /s at 40°C mm ² /s at 100°C	65 9.8
Viscosity, Cold Crank, °C/mPa.s	-25/5100
Viscosity, MRV, °C/mPa.s	-30/15,400
Viscosity Index	135
Flash Point, °C(°F)	232(450)
Pour Point, °C(°F)	-48(-54)
Sulfated Ash, mass %	0.96
Base Number, mgKOH/g, ASTM D2896	10.3
Phosphorus, mass %	0.076
Sulfur, mass %	0.28
Zinc, mass %	0.083

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

1 December 2016
HDMO-75